

图书基本信息

书名：<<纤维学会2009春季国际会议论文集>>

13位ISBN编号：9787506456357

10位ISBN编号：7506456354

出版时间：2009-5

出版时间：东华大学纺织学院 中国纺织出版社 (2009-05出版)

作者：东华大学纺织学院 编

版权说明：本站所提供下载的PDF图书仅提供预览和简介，请支持正版图书。

更多资源请访问：<http://www.tushu007.com>

## 内容概要

《纤维学会2009春季国际会议论文集（英文）（套装上下册）》是与2009国际纤维学会年会配套出版的论文集，本次会议由美国纤维学会主办，东华大学协办。

论文集共收录了国内外四百余篇关于纺织纤维、材料等方面的最新研究动态及成果论文，分上下两卷，共由9部分组成，分别是高分子及纳米技术，纺织加工技术，印染、后整理和生物技术，医用纺织品，功能和智能纺织品，纺织检测，产业用纺织品，时装设计、纺织史与纺织美学，零售、市场营销与管理。

全部采用英文编写，并由IsTP收录。

可供从事纺织、纤维材料、印染等行业的科研、教育等相关人士阅读、参考。

## 书籍目录

Section A Industrial Textiles  
Fibre- to- fibre Contacts in Nonwovens  
Filtration Behavior of An Original Two - layered Nonwoven Geotextile  
Mechanical Properties of Novel Stitched 3D Hybrid Basalt Composite  
Mechanical Properties of Novel Different Stitched Density 3D Hybrid Basalt Composite  
The Study on the Air Content of Electrospun Nanofiber Nonwoven Fabric  
Determine Pore Size Distribution in Nonwoven Fabrics  
Measurement of the Dynamic Permeability of Airbag Fabrics  
Porous Characteristics of Electrospun PLLA Microfiber/Nonwoven Fibrous Filter Composite Mats  
Liquid Absorption Properties of Super Absorbent Fiber Based on Acrylic Copolymers  
Synthesis and Characterization of Sulfonated Polysulfone Proton Exchange Membrane for Fuel Cells  
Study of Adhesion Property between PTFE Films and Polypropylene Spunbond Nonwoven Materials  
The Ageing of Polypropylene Geotextiles under Outdoor Environment  
Scenario Simulations of Nonwoven Webs and Fabrics  
Stability Analysis of Nonlinear Transverse Vibration of Paper Making Felt  
Research on Shear Performance of Tackified Woven Fabrics  
Optimization of Fibrous Insulation  
Processing, Structure and Properties of Melt Blown Poly Lactic Acid Nonwoven Fabrics  
Filtration Performance Optimization of Multi - layered Nonwoven Materials  
Thermal Bonding of Polypropylene  
Improving Phosphate Glass Fibre Performance in Composites  
Improved Performance of Bag Filters Through Fabric Surface Modification  
Effect of High Frequency Vibration on the Drawing Behavior of Staple Fiber Strands  
High - performance Synthetic Ropes for Tugs  
Study of Physical Characteristics of Industrial Filter Bag  
Morphology Effects on Effective Properties of Multiphase Materials  
Section B Processing Technology  
Aerodynamic Analysis for the Venturi of Pneumatic Yarn Knotting Devices  
Analysis on Tensile Property of Polyester/Cotton/Silk Tri - component Sirofil Composite Yarn  
Application of an Adaptive Neuro - fuzzy System for Predicting Rotor Spinning Yam Quality Properties  
Characteristics and Technology Optimizing of Core - spun Yarns on Rotor Spinning Frame  
Design and Weaving of the Shape - woven Preform Fabrics Used for Integral Composite Pressure Vessel Winding  
Differences in the Structure and Thermal Properties of Natural Colored Cottons and Bombax Cotton  
Effect of Calcium Salt Treatment on the Structure and Properties of Tussah Silk and Mulberry Silk  
ESR Signals from Wool Fibers Treated by DBD Plasma  
Investigation of the Mechanical and Thermodynamic Properties of a Modified PAN Fiber - Fe ( III ) Complex  
New Development of Whisk Broom Fiber and Its Use in Composite Products  
Numerical Study of Field Strength at Compact Groove in Compact Spinning with Inspiratory Groove  
Preparation of Cellulose/Soy Protein Isolate Blend Bio - fibers via Direct Dissolving Approach  
Preparation of Wool - Fe ( III ) Complex Catalyst and Its Application in Degradation of Acid Black  
Research on Enzyme Boiling Out and Bleaching Technology Based on Flax Roving  
Spinability of Domestic New Star Fine Denier Meta - aramid Fibre.....

## 章节摘录

插图：Three-point flexural test results As shown in figure 4, for the deflection along the wale direction and course direction, the composite PKFW is observed with biggest deflection among the three composites, which is attributed to the larger deformation subjected to the flexural load at the center of sample, compared with woven fabric. For the flexural stress along the two directions, composite WFPK is observed with the higher flexural stress than that of composite PKFW, and both of them are lower along the wale direction and higher in course direction than that of composite WFOK. There exists one difference between flexural specific energy along the wale direction and course direction. Composite WFPK shows the higher flexural specific energy than composite WFOK in wale direction and lower in course direction, however, Composite PKFW ranks between them two along both wale direction and course direction. In all the curves including the wale direction and course direction, the stair-like deformation trend can be observed when subjected to the three-point flexural tests. This exactly represents the failure process from the beginning to break. At the beginning, the sample undergoes one linear deformation. From then on the slope of the curves slows down due to the cracks occurred and grew on the matrix. One sharp drop is observed after the peak stress because of the break of woven layer with the comparatively lower strain at break. The flexural stress increases a little during the break of knitting layer reinforcement whereas some curves show this wholly and some partly.

编辑推荐

《纤维学会2009春季国际会议论文集(英文)(套装共2册)》：Host by , The Fiber Society, USA , Donghua University, PR China , Organized by , College of Textiles, Donghua University , Key Laboratory of Textile Science and Technology, Ministry of Education, China , Engineering Research enter for Industrial Textiles, Ministry of Education, China , Co-organized by , State Key Laboratory for Modification of Chemical Fibers , Key Laboratory of Science & Technology of Eco-Textiles, Ministry of Education, China , National Engineering Research Center for Dyeing & Finishing of Textiles.

版权说明

本站所提供下载的PDF图书仅提供预览和简介，请支持正版图书。

更多资源请访问:<http://www.tushu007.com>