

<<DL/T51812003 水电水利工>>

图书基本信息

书名：<<DL/T51812003 水电水利工程锚喷支护施工规范>>

13位ISBN编号：9787508382159

10位ISBN编号：7508382153

出版时间：2009-3

出版时间：中国电力出版社

作者：中华人民共和国国家经济贸易会 编

页数：70

字数：60000

版权说明：本站所提供下载的PDF图书仅提供预览和简介，请支持正版图书。

更多资源请访问：<http://www.tushu007.com>

<<DL/T51812003 水电水利工>>

内容概要

《DL/T5181-2003 水电水利工程锚喷支护施工规范（英文版）》为英文版，主要内容有：Scope、Normative References、Terms and Definitions、General、Construction of Anchor Bars、General、Anchor Bar Bonded in Full Length、Tension Anchor Bar、Friction Anchor Bar、ubeAnchor Bar and Self-drilling Grouted Anchor Bar、Prestressed Tendon Construction等等。

书籍目录

Foreword1 Scope2 Normative References3 Terms and Definitions4 General5 Construction of Anchor Bars 5.1
General 5.2 Anchor Bar Bonded in Full Length 5.3 Tension Anchor Bar 5.4 Friction Anchor Bar 5.5
TubeAnchor Bar and Self-drilling Grouted Anchor Bar6 Prestressed Tendon Construction7 Shotcrete
Construction 7.1 Raw Materials 7.2 Construction Equipment 7.3 Mix Proportion, Mixing and Delivery
7.4 Preparation Prior to Shotcreting 7.5 Shotcreting 7.6 Sand-enveloped-with-cement Shotcrete 7.7
Steel Fiber-reinforced Shotcrete8 Anchor and Shotcrete Support 8.1 Wire Mesh-reinforced Shotcrete 8.2
Steel Arch Rib and Wire Mesh for Shotcrete 8.3 Anchor and Shotcrete Support under Adverse Geological
Conditions9 Safety Technologies and Dust Prevention 9.1 Safety Technologies 9.2 Dust Prevention10
Quality Inspection 10.1 Anchor Bar and Tendon 10.2 ShotcreteAppendix A (Normative Appendix) Methods
for Monitoring and Survey of Anchor and Shotcrete SupportAppendix B (Informative Appendix) Testing
Method for Grouting CompactnessAppendix C (Normative Appendix) Measurement Method for Dust
Concentration in Shotcrete Working AreaAppendix D (Informative Appendix) Testing Method for Pullout
Resistance of Anchor BarAppendix E (Normative Appendix) Testing Methods for Compressive Strength of
ShotcreteAppendix F (Normative Appendix) Testing Method for Anti-seepage Indexes of ShotcreteAppendix G
(Normative Appendix) Testing Method for Shotcrete Tensile StrengthAppendix H (Normative Appendix)
Testing Method for Frost Resistance of ShotcreteAppendix I (Normative Appendix) Testing Methods for Bond
Strength of Shotcrete and Surrounding Rock

章节摘录

插图：8 During grouting , if grout leakage occurs in inner anchorage section due to breaking of grout stop ring , the tendon shall be pulled out so as to flush away the grout in hole with clear water, replace the grout stop ring , re-install the tendon and conduct grouting in the inner anchorage section.

6.0.6 Relevant regulations for tensioning and locking of tendon : 1 Test in-situ shall be conducted for tensioning of anchor bars so as to determine reasonable tensioning techniques , to verify the tensioning parameters and to avoid compulsory tensioning. 2 Before tensioning , tensioning equipment shall be calibrated. 3 Tendon tensioning shall be conducted according to specified procedures. Tensioning procedure shall be designed by considering the mutual influence of adjacent tendons during tensioning. 4 Before the formal tensioning , pre-tensioning shall be conducted once or twice with single-tendon jack to keep each part in tight contact and steel wire or steel strand straight. The pre-tensioning load may be 20%—30% of the designed tensioning load. 5 During the formal tensioning , tensioning and pressure stabilizing shall be made according to the designed load increasing range and the stabilizing duration , and then locking shall be conducted. If the load increasing range and the duration of pressure stabilizing are not specified in design , the tensioning load shall be increased to 1.10% of the design one , and then the stabilizing pressure shall be kept at least 2min before locking. 6 Within 48 h after locking , if loss of prestress is larger than 10% of the design load , compensation tensioning shall be made.

<<DL/T51812003 水电水利工>>

编辑推荐

《DL/T5181-2003 水电水利工程锚喷支护施工规范(英文版)》由中华人民共和国国家经济贸易委员会发布。

版权说明

本站所提供下载的PDF图书仅提供预览和简介, 请支持正版图书。

更多资源请访问:<http://www.tushu007.com>